

emballator

Packaging solutions for future generations

Product specification 44-205

Utfärdad av Carl Johan Bonde	Godkänd av Carl Johan Bonde	Verifierad av Leila Moshayyadi	Datum 2025-10-29	Dokument nr. PS-205-44-1	Utgåva 4
---------------------------------	--------------------------------	-----------------------------------	---------------------	-----------------------------	-------------

Product:	44-205	
Article number:	Please contact our sales department.	
Product description:	44mm roll-on closure available in glossy or matte finish.	
Technical specifications		
Drawings:	Please contact our sales department.	
Plastic resin:	PP	
Master batch:	Please contact our sales department.	
Recommended capping torque:	1,2-1,5 Nm	
Recommended storage conditions and time for the packaging material:	Temperature: 15-30 °C If the products have been stored under or over these temperature conditions, they must be conditioned at 15-30°C for 24 hours before processing. Humidity: 30-70%	
Storage durability:	2 years, keep room temperature in tightly sealed cardboard boxes.	
Quality Control		
Standards and norms:	Sampling procedure: SS 020130-ISO2859 normal 1. Defect classes according to KP-002.	
Delivery		
Packaging:	700 pcs packed in plastic bag, packed in cardboard boxes 82dm³. Labels on the boxes. 16 boxes on each pallet with stretch film wrapped around.	
Traceability:	Marking for traceability contains EVAB article number, customer article number, production order number, pieces per carton, EVAB order number customer order number and date and signature.	