

emballator

Packaging solutions for future generations

Product specification 33-261

Utfärdad av Fredrik Wernersson	Godkänd av Carl Johan Bonde	Verifierad av Carl Johan Bonde	Datum 2025-11-11	Dokument nr. PS-261-33	Utgåva 3
--------------------------------------	--------------------------------	-----------------------------------	---------------------	---------------------------	-------------

Product:	33-261	
Article number:	Please contact our sales department.	
Product description:	Screw cap GPI 33mm with EPE liner and aluminum shell cover.	
Technical specifications		
Drawings:	Product drawing: S 33-261 dated 2015-11-27 Neck drawing: Emballator 12589	
Sealing:	Liner 30,10 X1,5 350	
Plastic resin:	PP	
Adhesive:	Added between plastic insert and aluminum cover.	
Recommended capping torque:	1,9 Nm ±0,1	
Recommended storage conditions and time for the packaging material:	Temperature:15-30 °C If the products have been stored under or over these temperature conditions, they must be conditioned at 15-30°C for 24 hours before processing. Humidity: 30-70%	
Storage durability:	1 year, keep at room temperature in tightly sealed carboard boxes.	
Quality Control		
Standards and norms:	Sampling procedure: SS 020130-ISO2859 normal 1. Defect classes according to KP-002.	
Certificate of conformance:	N/A	
Delivery		
Packaging:	2200 pcs packed in plastic bag, packed in cardboard boxes 380 x380 x 325mm Labels on the boxes. 24 boxes on each pallet with stretch film wrapped around.	
Traceability:	Marking for traceability contains EVAB article number, customer article number, production order number, pieces per carton, EVAB order number customer order number and date and signature.	